

Premium Phantom Cables 3-Pin XLR DMX Male To Female Cable

This premium 3-pin DMX lighting cable has a 3-pin XLR male on one end and a 3-pin XLR female on the other. It is typically used to control stage lighting and effects.

- Constructed true 110 ohm cable for quick response time movement
- Dual shielding includes a 100% aluminum/mylar foil, plus a 95% tinned copper braid
- 100% aluminum/mylar foil shield for superior EMI and RFI rejection
- High quality, heavy duty premium strain relief connectors optimizes connectivity and maintains a clear signal integrity
- Lead Free, "silver laced" solder is used in order to reduce loss and maximize conductivity
- Standard Color Kinetics ColorBlast® pinout.

Physical Characteristics

Shielded	100% Aluminum/Mylar Foil Shield, 65% Braid
Color	Black Cable, Nickel Plated Connectors, Gold Plated Pins
Cable Diameter	7.1mm
Cable Temperature Rating	-30 deg C to 75 deg C

Performance

Impedance	110 Ohms
-----------	----------

Connector(s)

Connector A	3-pin XLR Male
Connector B	3-pin XLR Female

Packaging Information

Packaging Quantity	1 Cable
--------------------	---------

Warranty Information

Warranty	Lifetime Limited
----------	------------------



Part number	Standard lengths
DMX-3MF-01.5	1.5 foot
DMX-3MF-03	3 foot
DMX-3MF-06	6 foot
DMX-3MF-10	10 foot
DMX-3MF-15	15 foot
DMX-3MF-25	25 foot
DMX-3MF-35	35 foot
DMX-3MF-50	50 foot
DMX-3MF-75	75 foot
DMX-3MF-100	100 foot

Name	Premium Phantom Cables 3-Pin XLR DMX Male To Female Cable
P/N	DMX-3MF-xx