

# Premium Phantom Cables 3-Pin XLR DMX Male To Male Cable

This premium 3-pin DMX lighting cable has a 3-pin XLR male on one end and a 3-pin XLR male on the other. It is typically used to control stage lighting and effects.

- Constructed true 110 ohm cable for quick response time movement
- Dual shielding includes a 100% aluminum/mylar foil, plus a 95% tinned copper braid
- 100% aluminum/mylar foil shield for superior EMI and RFI rejection
- High quality, heavy duty premium strain relief connectors optimizes connectivity and maintains a clear signal integrity
- Lead Free, "silver laced" solder is used in order to reduce loss and maximize conductivity
- Standard Color Kinetics ColorBlast® pinout.

## Physical Characteristics

Shielded	100% Aluminum/Mylar Foil Shield, 65% Braid
Color	Black Cable, Nickel Plated Connectors, Gold Plated Pins
Cable Diameter	7.1mm
Cable Temperature Rating	-30 deg C to 75 deg C

## Performance

Impedance	110 Ohms
-----------	----------

## Connector(s)

Connector A	3-pin XLR Male
Connector B	3-pin XLR Male

## Packaging Information

Packaging Quantity	1 Cable
--------------------	---------

## Warranty Information

Warranty	Lifetime Limited
----------	------------------



Part number	Standard lengths
DMX-3MM-01.5	1.5 foot
DMX-3MM-03	3 foot
DMX-3MM-06	6 foot
DMX-3MM-10	10 foot
DMX-3MM-15	15 foot
DMX-3MM-25	25 foot
DMX-3MM-35	35 foot
DMX-3MM-50	50 foot
DMX-3MM-75	75 foot
DMX-3MM-100	100 foot

Name	Premium Phantom Cables 3-Pin XLR DMX Male To Male Cable
P/N	DMX-3MM-xx